



QL DLS4.8W 3528-V2-18



SPECIFICATIONS

Led	18 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	4 mm W x 300 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.12 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	50 mm
Pcb	FR4
Power	1.44 Watt / Module

FEATURES

High brightness single color led strip
3528 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Architectural decorative lighting

LED SPECIFICATIONS

7-9 Lm

High luminous intensity

SMD (top view) type

High brightness 1 chip LED

Package size: 3.5 X 2.8 X 0.95 mm

12DC VOLT

60 LED/M

4.8 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS6.72W 3528-V1-24



SPECIFICATIONS

Led	24 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	4 mm W x 296 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.16 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	37 mm
Pcb	FR4
Power	1.92 Watt / Module

FEATURES

High brightness single color led strip
3528 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Architectural decorative lighting

LED SPECIFICATIONS

7-9 Lm

High luminous intensity

SMD (top view) type

High brightness 1 chip LED

Package size: 3.5 X 2.8 X 0.95 mm

12DC VOLT

84 LED/M

6.72 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS6.72W 3528-V4-42



SPECIFICATIONS

Led	42 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	4 mm W x 500 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.28 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	35.71 mm
Pcb	FR4
Power	3.36 Watt / Module

FEATURES

High brightness single color led strip
3528 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Prestigious private residences, Villa's
Cruise Ships and yachts
Architectural decorative lighting

LED SPECIFICATIONS

7-9 Lm

Package size: 3.5 X 2.8 X 0.95 mm

High brightness 1 chip LED

SMD (top view) type

High luminous intensity

12DC VOLT

84 LED/M

6.72 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS8.16W 3528-V3-30



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	5 mm W x 294 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.2 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	29.4 mm
Pcb	FR4
Power	2.4 Watt/ Module

FEATURES

High brightness single color led strip
3528 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Architectural decorative lighting

LED SPECIFICATIONS

7-9 Lm

Package size: 3.5 X 2.8 X 0.95 mm

High brightness 1 chip LED

SMD (top view) type

High luminous intensity

12DC VOLT

102 LED/M

8.16 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
SLIDER			EDGE		
TOP 1828			TUB		
DECOR			NEPTUNE		
HELIOS			TOP 5070		
VESSEL			MOON		
CABI-LITE			TOP 3567		
			CARONA		

QL DLS5.76W 3528-V9



SPECIFICATIONS

Led	36 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	8 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.24 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	41.25 mm
Pcb	FR4
Power	2.88 Watt / Module

FEATURES

High brightness single color led strip
3528 SMT package
High luminous intensity
Long life
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Prestigious private residences, Villa's
Cruise Ships and yachts
Architectural decorative lighting

LED SPECIFICATIONS

7-9 Lm

Package size: 3.5 X 2.8 X 0.95 mm

High brightness 1 chip LED

SMD (top view) type

High luminous intensity

12DC VOLT


72 LED/M

5.76 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			EDGE		
SLIDER			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS19.2W 3528-120-24W



SPECIFICATIONS

Led	120 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 24 VOLT
Current	0.4 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	24.75 mm
Pcb	FR4
Power	9.6 Watt / Module

FEATURES

High brightness single color led strip
3528 SMT package
Very high luminous intensity
Long life
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Pools & Gymsnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Furniture, under cabinet lighting
This LED strip is must be used with proper heat sink

LED SPECIFICATIONS

7-9 Lm

Package size: 3.5 X 2.8 X 0.95 mm

High brightness 1 chip LED

SMD (top view) type

High luminous intensity

24DC VOLT

240 LED/M

19.2 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					



QL DLS4.8W 3014-V6-30



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW
Size	4 mm W x 500 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.2 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	50 mm
Pcb	FR4
Power	2.44 Watt / Module

FEATURES

High brightness single color led strip
3014 OSRAM DURIS E3 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Architectural decorative lighting

LED SPECIFICATIONS

9-12 Lm

Package size: 3.0 X 1.4 X 1.2 mm

High brightness 1 chip LED from OSRAM

SMD (top view) type











































High luminous intensity

12DC VOLT

60 LED/M

4.8 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS4.8W 3014-V5-18



SPECIFICATIONS

Led	18 LED / module
Colors	CW/NW/WW
Size	4 mm W x 300 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.12 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	50 mm
Pcb	FR4
Power	1.44 Watt / Module

FEATURES

High brightness full color led strip
3014 OSRAM DURIS E3 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Architectural decorative lighting

LED SPECIFICATIONS

9-12 Lm

Package size: 3.0 X 1.4 X 1.2 mm

High brightness 1 chip LED from OSRAM

SMD (top view) type

High luminous intensity

12DC VOLT

60 LED/M

4.8 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS5.76W 3014-V7-36



SPECIFICATIONS

Led	36 LED / module
Colors	CW/NW/WW
Size	4 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.24 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	41.25 mm
Pcb	FR4
Power	2.88 Watt / Module

FEATURES

High brightness single color led strip
3014 SMT package [30mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Casinos, bars, Clubs & Entertainment
Prestigious private residences, Villa's
Cruise Ships and yachts
Architectural decorative lighting

LED SPECIFICATIONS

9-12 Lm

Package size: 3.0 X 1.4 X 0.70 mm

High brightness

SMD (top view) type

High luminous intensity

12DC VOLT

72 LED/M

5.76 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS9.6W 3014-TWIN



SPECIFICATIONS

Led	84 LED / module
Colors	CW/NW/WW
Size	8 mm W x 700 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.56 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	50 mm
Pcb	FR4
Power	6.72 Watt / Module

FEATURES

High brightness single color dual line led strip
3014 OSRAM DURIS E3 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Airports and Bus Stations
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

9-12 Lm

Package size: 3.0 X 1.4 X 1.2 mm

High brightness 1 chip LED from OSRAM

SMD (top view) type

High luminous intensity

12DC VOLT

120 LED/M


9.6 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			EDGE		
SLIDER			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		



QL DLS7.2W 1050-15S



SPECIFICATIONS

Led	15 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	10 mm W x 500 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.3 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	100 mm
Pcb	FR4
Power	3.6 Watt / Module

FEATURES

High brightness single color led strip
5050 SMT package [60mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20mA each]

SMD (top view) type

High luminous intensity

12DC VOLT

30 LED/M

7.2 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

Led	18 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	6 mm W x 294 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.36 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	49 mm
Pcb	FR4
Power	4.32 Watt / Module

- High brightness single color led strip
- 5050 SMT package [60mA]
- High luminous intensity
- Slim design
- High reliability
- Solid state, high shock, vibration resistant
- Maintenance free, easy installation, long life
- Very low power consumption and low heat
- Good thermal conductivity
- Easy to pack, ship and install

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Casinos, bars, Clubs & Entertainment
Retail shops, Malls & food plaza's
Architectural decorative lighting

High luminous intensity

14.4 WATT/M

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
SLIDER			EDGE		
TOP 1828			TUB		
DECOR			NEPTUNE		
HELIOS			TOP 5070		
VESSEL			MOON		
CABI-LITE			TOP 3567		
			CARONA		

QL DLS8.64W DT5050L18-DC24



SPECIFICATIONS

Led	18 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	10 mm W x 500 mm L x 1.6 mm H
Input Voltage	DC 24 VOLT
Current	0.18 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	166.66 mm
Pcb	Fr4
Power	4.32 Watt / Module

FEATURES

High brightness single color led strip
5050 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20mA each]

SMD (top view) type

High luminous intensity

24DC VOLT

36 LED/M

8.64 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS14.4W 1050-30S



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW/R/G/B/A
Size	10 mm W x 500 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.6 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	50 mm
Pcb	Fr4 / Aluminum
Power	7.2 Watt / Module

FEATURES

High brightness single color led strip
5050 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

SMD (top view) type

High luminous intensity

12DC VOLT

60 LED/M

14.4 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		



QL DLS19.2W 5630-30



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.8 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	49.5 mm
Pcb	Aluminum
Power	9.6 Watt / Module

FEATURES

High brightness single color led strip
5630 OSRAM SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with aluminum PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's
This LED strip is must be used with proper heat sink

LED SPECIFICATIONS

38-45 Lm

Package size: 5.6 X 3.0 X 0.87 mm

High brightness chip from OSRAM LED

SMD (top view) type

High luminous intensity

12DC VOLT

60 LED/M

19.2 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS19.2W 5630-30-24X



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 24 VOLT
Current	0.4 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	99 mm
Pcb	Aluminum
Power	9.6 Watt / Module

FEATURES

High brightness single color led strip
5630 OSRAM SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with Aluminum PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's

LED SPECIFICATIONS

38-45 Lm

Package size: 5.6 X 3.0 X 0.87 mm

High brightness chip from OSRAM LED

SMD (top view) type

High luminous intensity

24DC VOLT

60 LED/M

19.2 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS11.52W 1224-5630-180S



SPECIFICATIONS

Led	18 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT / DC 24 VOLT
Current	0.48 A / 0.24 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	82.5 mm / 165 mm
Pcb	FR4
Power	5.76 Watt / Module

FEATURES

High brightness single color led strip
5630 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Offices, & Apartments
Retail shops, Malls & food plaza's
Architectural decorative lighting
Furniture, under cabinet lighting

LED SPECIFICATIONS

38-45 Lm

Package size: 5.6 X 3.0 X 0.87 mm

High brightness chip from OSRAM LED

SMD (top view) type

High luminous intensity

12DC VOLT

36 LED/M

11.52 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS9.6W 5630-15



SPECIFICATIONS

Led	15 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.4 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	99 mm
Pcb	FR4
Power	4.8 Watt / Module

FEATURES

High brightness single color led strip
5630 OSRAM SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with Fr4 PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's
This LED strip is must be used with proper heat sink

LED SPECIFICATIONS

38-45 Lm

Package size: 5.6 X 3.0 X 0.87 mm

High brightness chip from OSRAM LED

SMD (top view) type

High luminous intensity

12DC VOLT


30 LED/M

9.6 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS23.04W 5730-72



SPECIFICATIONS

Led	36 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.96 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	41.25 mm
Pcb	Aluminum
Power	11.52 Watt / Module

FEATURES

High brightness single color led strip
5730 SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with Aluminum PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Offices, & Apartments
Museums and Cinemas, smart Homes
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's
This LED strip is must be used with proper heat sink

LED SPECIFICATIONS

38-45 Lm
Package size: 5.7 X 3.0 X 0.87 mm
High brightness chip LED
SMD (top view) type
High luminous intensity

12DC VOLT

72 LED/M

23.04 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS30-45W 5630CC-PL6



SPECIFICATIONS

Led	10 LED / module
Colors	CW/NW/WW
Size	10 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 30-34 VOLT
Current	100mA - 140mA
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	495 mm
Pcb	Aluminum
Power	30-45 Watt

FEATURES

High brightness single color led strip
5630 OSRAM SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with Aluminum PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Offices, & Apartments
Hospitals & Shopping Centre's
Warehouses and commercial premises
Educational Institutes, Training Centre's
Airports and Bus Stations
Small & Medium workshops
Retail shops, Malls & food plaza's
This LED strip is must be used with proper heat sink

LED SPECIFICATIONS

38-45 Lm
Package size: 5.6 X 3.0 X 0.87 mm
High brightness chip from OSRAM LED
SMD (top view) type
High luminous intensity

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS2.4W OPERA



SPECIFICATIONS

Led	6 LED / module
Colors	CW/NW/WW
Size	10 mm W x 270 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.2 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	270 mm
Pcb	FR4
Power	2.4 Watt / Module

FEATURES

High brightness single color led strip
5630 OSRAM SMT package
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity with high quality FR4 PCB
Easy to pack, ship and install with thermal conductive tape

APPLICATIONS

Hotels, resorts & Restaurants
Retail shops, Malls & food plaza's
Furniture, under cabinet lighting

LED SPECIFICATIONS

38-45 Lm

Package size: 5.6 X 3.0 X 0.87 mm

High brightness chip from OSRAM LED

SMD (top view) type

High luminous intensity

12DC VOLT

6 LED/
Module


2.4 WATT/
Module

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		



QL DLS7.2W 2835-15



SPECIFICATIONS

Led	15 LED / module
Colors	CW/NW/WW
Size	8 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.3 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	99 mm
Pcb	FR4
Power	3.6 Watt / Module

FEATURES

High brightness single color led strip
2835 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Museums and Cinemas, smart Homes
Educational Institutes, Training Centre's
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

22-24 Lm

Package size: 2.8 X 3.5 X 0.75 mm

High brightness

SMD (top view) type

High luminous intensity

12DC VOLT

30 LED/M

7.2 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			EDGE		
SLIDER			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS14.4 W 2835-30



SPECIFICATIONS

Led	30 LED / module
Colors	CW/NW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.6 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	49.5 mm
Pcb	FR4
Power	7.2 Watt / Module

FEATURES

High brightness single color led strip
2835 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Museums and Cinemas, smart Homes
Educational Institutes, Training Centre's
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

22-24 Lm

Package size: 2.8 X 3.5 X 0.75 mm

High brightness

SMD (top view) type

High luminous intensity

12DC VOLT


60 LED/M

14.4 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS11.52W 2835-24AR



SPECIFICATIONS

Led	24 LED / module
Colors	CW/NW/WW
Size	8 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.48 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	61.87 mm
Pcb	FR4
Power	5.76 Watt / Module

FEATURES

High brightness single color led strip
2835 SMT package [60mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Museums and Cinemas, smart Homes
Educational Institutes, Training Centre's
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

22-24 Lm

Package size: 2.8 X 3.5 X 0.75 mm

High brightness 1 chip LED

SMD (top view) type

High luminous intensity

12DC VOLT

48 LED/M

11.52 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			EDGE		
SLIDER			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS11.52W 2835-24



SPECIFICATIONS

Led	24 LED / module
Colors	CW/NW/WW
Size	4 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.48 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	61.87 mm
Pcb	FR4
Power	5.76 Watt / Module

FEATURES

High brightness single color led strip
2835 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Offices, & Apartments
Museums and Cinemas, smart Homes
Educational Institutes, Training Centre's
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

22-24 Lm

Package size: 2.8 X 3.5 X 0.75 mm

High brightness

SMD (top view) type

High luminous intensity

12DC VOLT

48 LED/M

11.52 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
NANO			EDGE		
SLIM 45			TUB		
SLIDER			NEPTUNE		
TOP 1828			TOP 5070		
DECOR			MOON		
HELIOS			TOP 3567		
VESSEL			CARONA		
CABI-LITE					

QL DLS28.8W 2835-CWW2



SPECIFICATIONS

Led	60 LED / module
Colors	CW/WW
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	1.2 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	49.5 mm
Pcb	FR4
Power	14.4 Watt / Module

FEATURES

High brightness dual color led strip
2835 SMT package [60 mA]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Cruise Ships and yachts
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

22-24 Lm

Package size: 2.8 X 3.5 X 0.75 mm

High brightness

SMD (top view) type

High luminous intensity

12DC VOLT

120 LED/M

28.8 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

Rigid LED PCB

QL RPCB 2835


24DC

Volts

15

WATT/mt

STRIP MODULE



Specification

CCT	3000K	4000K	6000K
LED	120 LED / mt	120 LED / mt	120 LED / mt
Efficacy	118lm/W	135lm/W	135lm/W
Size	W: 10mm x H: 1.6mm x L: 1000mm	W: 10mm x H: 1.6mm x L: 1000mm	W: 10mm x H: 1.6mm x L: 1000mm
Input Voltage	24V DC	24V DC	24V DC
Current	0.625 A	0.625 A	0.625 A
Beam Angle	120°	120°	120°
Operating Temperature	-20° ~ +70°	-20° ~ +70°	-20° ~ +70°
PCB	Aluminium	Aluminium	Aluminium
Power	15W/ mt	15W/ mt	15W/ mt

































Features

- High Brightness Single Color LED Strip 2835 Osram Duris SMT Package
- High Luminous Intensity
- Slim Design
- High Reliability
- Solid State, High Shock, Vibration Resistant
- Maintenance Free, Easy installation, Long Life, High CRI Ra > 90
- Very Low power Consumption & Low Heat
- Good thermal conductivity
- Easy to pack, shop & install

Details

- High Brightness
- SMD (top view) type
- High Luminous Intensity
- Rigid PCB, Flexible Circuit Board

Aluminum Profiles Available


NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			ZOOM		



QL DLS14.4W 6350-RGB



**QL DLS14.4W 6350-RGB
STRIP MODULE**



SPECIFICATIONS

Led	18 LED / module
Colors	RGB
Size	6 mm W x 294 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.36 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	49 mm
Pcb	FR4
Power	4.32 Watt / Module
Controller	Standard RGB controller

FEATURES

High brightness RGB full color led strip
5050 SMT package [RGB 20 mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

RGB SMD (top view) type

High luminous intensity

12DC VOLT

60 LED/M

14.4 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			ELITE		
SLIDER			EDGE		
TOP 1828			TUB		
DECOR			NEPTUNE		
HELIOS			TOP 5070		
VESSEL			MOON		
CABI-LITE			TOP 3567		
			CARONA		

QL DLS11.52W 5050-RGB48



SPECIFICATIONS

Led	24 LED / module
Colors	RGB
Size	12 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 24 VOLT
Current	0.24 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	123.75 mm
Pcb	FR4
Power	5.76 Watt / Module
Controller	Standard RGB controller

FEATURES

High brightness full RGB color led strip
5050 SMT package [RGB 20 mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

RGB SMD (top view) type

High luminous intensity

24DC VOLT

48 LED/M

11.52 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ANGULAR 45		
GRACE			EDGE		
GROOVY			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE					

QL DLS14.4W 5050-PNL-55



SPECIFICATIONS

Led	33 LED / module
Colors	RGB
Size	8 mm W x 550 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.66 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	50 mm
Pcb	FR4
Power	7.92 Watt / Module
Controller	Standard RGB controller

FEATURES

High brightness RGB full color led strip
5050 SMT package [RGB 20 mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

RGB SMD (top view) type

High luminous intensity

12DC VOLT


60 LED/M

14.4 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
MASTER			ART		
GRACE			ANGULAR 45		
GROOVY			EDGE		
SLIDER			TUB		
TOP 1828			NEPTUNE		
DECOR			TOP 5070		
HELIOS			MOON		
VESSEL			TOP 3567		
CABI-LITE			CARONA		

QL DLS11.52W 1550-PC-RGB-1



SPECIFICATIONS

Led	24 LED / module
Colors	RGB point control with UCS1903B
Size	15 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 12 VOLT
Current	0.48 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cutttable Size	61.87 mm
Pcb	FR4
Power	5.76 Watt / Module
Controller	Programmable RGB controller & DMX

FEATURES

High brightness RGB full color led strip
Point control with DMX and standard RGB controllers
5050 SMT package [RGB 20 mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

RGB SMD (top view) type

High luminous intensity

12DC VOLT

48 LED/M

11.52 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
GROOVY			TOP 5070		
HELIOS					
VESSEL					

QL DLS14.4W 1550-PC-RGB-2



SPECIFICATIONS

Led	24 LED / module
Colors	RGB point control chip in LED
Size	15 mm W x 495 mm L x 1.6 mm H
Input Voltage	DC 5 VOLT
Current	1.44 A
Beam Angle	120°
Operating Temp	-20° ~ +60°
Cuttable Size	61.87 mm
Pcb	FR4
Power	7.2 Watt / Module
Controller	Programmable RGB controller & DMX

FEATURES

High brightness single color led strip
Point control with DMX and standard RGB controllers
5050 SMT package [RGB 20 mA each]
High luminous intensity
Slim design
High reliability
Solid state, high shock, vibration resistant
Maintenance free, easy installation, long life
Very low power consumption and low heat
Good thermal conductivity
Easy to pack, ship and install

APPLICATIONS

Sign & display, Light box, edge lighting
Hotels, resorts & Restaurants
Conference Halls and Galleries
Casinos, bars, Clubs & Entertainment
Museums and Cinemas, smart Homes
Prestigious private residences, Villa's
Pools & Gymnasiums & Big Health Clubs
Retail shops, Malls & food plaza's
Luxury showrooms & Studios
Architectural decorative lighting

LED SPECIFICATIONS

18-20 Lm

Package size: 5.0 X 5.0 X 1.4 mm

High brightness 3 chip LED [20 mA each]

RGB SMD (top view) type

High luminous intensity

5DC VOLT

48 LED/M

14.4 WATT/M

Aluminum Profiles Available

NAME	IMAGE	CROSS SEC.	NAME	IMAGE	CROSS SEC.
GROOVY			TOP 5070		
HELIOS					
VESSEL					

QL DLS-RECESSED LINEAR LIGHT



RECESSED LINEAR LIGHT

TECHNICAL SPECIFICATIONS

- Material: Aluminium
- PCB: Aluminium 1.6mm
- End caps - Aluminium
- Size: 90 mm x 18 mm [W x H]
- Max PCB size possible: 24 mm
- Max length: 2400 mm
- Diffuser: press fit [Non-yellowing, BWF made]
- Watts: 18 w & 35 w
- Finish: Raw / Anodized or Powder coated [Custom]

AVAILABLE STANDARD MODELS



18 Watts / 2 module

Size: 1200 mm x 90 mm

Working Current : 350 mA

Driver: 18 W



35 Watts / 2 modules

Size: 2400 mm x 90 mm


Working Current: 700mA

Driver: 35 W

QL DLS-RECESSED LINEAR LIGHT

HELIOS PROFILE

A very new concept of modern cost saving lighting, come with Helios. Very elegant and efficient profile by DigiLED, designed for ceiling and wall recessed applications. Suitable for general lighting and decorative lighting, Helios is excellent heat sink medium for LED linear lighting. It can be customized for linear or square or other shapes for office and other commercial applications. The aluminum profile protects the light from being damaged or broken. They also protect from moisture and from unwanted handling of the lights.



WHY CHOOSE PC DIFFUSER ?

The damp-proof diffuser of Helios have been designed for the special ambient conditions presented by industrial manufacturing. An impact-resistant diffuser of PC with high quality prismatic technology and a special sealing system provide protection against extreme temperatures, critical humidity conditions and difficult ambient conditions. High quality diffuser make the luminaire highly reliable. This special diffuser offers wide and glare-restricted light distribution on the working plane and ceiling. What's more, the diffuser can be removed or installed without removing or disturbing the profile mounting for any additional maintenance in future




CONSTANT CURRENT MODULE

Module Specifications: Constant Current driven LED module : DGST-3014-96-D

DGST-3014-96-D	3014 / 60mA	Aluminium PCB	LED : 3014	Nos : 96
Series : 16	Parallel : 6	mA : 300-350	Voltage : 48	Beam Angle : 120°
CRI : 80-85	Ambient Temp. : -25...+45°C	LED : OSRAM DURIES E3	Warranty : 5 Years	
Lifetime [Wh] : 30,000	Colour Temperature : 3000K, 4000K, 6500K		Strip Dimensions : 595 L x 25 W x 1.6H	

Tape : PCB installed using Heat conductive tape

PCB for down-light



ACCESSORIES




ALUMINIUM END CAPS



EXTENSION CLIP



PRESS FIT BWF Acryl Satin, + colourLED®
(We do not use slide-in Acrylic)



Dimensions



Surge Protector



Down Side Light

QL DLS-ULTRALINE-SUSPENDED



TECHNICAL SPECIFICATIONS

- Material: Aluminium
- PCB: Aluminium 1.6mm
- End caps - Aluminium
- Size: 54 mm x 70 mm [W x H]
- Max PCB size possible: 24 mm
- Max length: 2400 mm
- Diffuser: press fit [Non-yellowing, BWF made]
- Watts: 35 w & 65 w
- Finish: Raw / Anodized or Powder coated [Custom]

QL DLS-ULTRALINE-SUSPENDED

CONSTANT CURRENT MODULE

Module Specifications: Constant Current driven LED module : DGST-3014-96-D

DGST-3014-96-D	3014 / 60mA	Aluminium PCB	LED : 3014	Nos : 96
Series : 16	Parallel : 6	mA : 300-350	Voltage : 48	Beam Angle : 120°
CRI : 80-85	Ambient Temp. : -25...+45°C	LED : OSRAM DURIES E3	Warranty : 5 Years	
Lifetime [Wh] : 30,000	Colour Temperature : 3000K, 4000K, 6500K	Strip Dimensions : 595 L x 25 W x 1.6H		
Tape : PCB installed using Heat conductive tape				

AVAILABLE STANDARD MODELS



35 Watts / 2 modules

Size: 1200 mm x 65 mm

Working Current : 700mA

Driver: 35 W



65 Watts / 4 modules

Size: 2400 mm x 65 mm

Working Current: 700mA

Driver: 65 W



ACCESSORIES



ALUMINIUM END CAPS




SUSPENSION ROPE



EXTENSION CLIP




PRESS FIT BWF Acryl Satin, + colourLED®
(We do not use slide-in Acrylic)



Dimensions



Surge Protector




Down Side Light



Up & Down Side Light

QL DLS-WARDROBE


“ No more dark in the Wardrobe ”



LED **EDISON 2835; 11.52W/m**


COLORS	Cool White / Natural White
LENGTH	18"/36"/42"/Costmised Size
WIDTH X HEIGHT	30 X 15 MM
INPUT VOLTAGE	DC 12 VOLT
BEAM ANGLE	120°
OPERATING TEMPERATURE	-20° ~ +60°
POWER	11.52 watt / Meter
FROSTED COVER	Pre Installed
ACCESSORIES	End Support / Center Support

DIMENSIONS [mm]



● **FEATURES:**

- High brightness
- Strong Aluminium material
- Silver Anodized / Wooden Textures
- Slim design
- Low Power Consumption
- Maintenance free



WOODEN TEXTURE PROFILE AVAILABLE



END SUPPORT



CENTER SUPPORT



Aluminium Profile

● **Application:**

This double function wardrobe profile can be used to hang cloths as well as illuminate the inside area. Mounting of this profile is possible on side walls using specially designed end supports.