



CEILING RECESSED DOWN LIGHTS



QL-MOD-A-05 9/12W



QL-MOD-B-05 15W/20W



QL-MOD-C-05 25W/30W



QL-MOD-D-05 35W/40W

Structure and characteristics:

OPTICS:

- CREE, BRIDGELUX COB module
- High lumen ,high CRI ,vivid & uniform lighting effect
- Multiple beam angle for choice
- High lumen output, accurate light distribution soft & comfortable light effect
- International high quality aluminum, die – cast heat sink, vortex. And convective dissipation technology
- Module design, adapted to different function and dimension of lamp housing
- Easy for disassembling, low stock but flexible fit to end market demands

Driver:

- External driver , optional
- Non –flicker for option

Front Case:

- International high quality die- cast aluminum
- Easy for all kind surface finishing
- Cold- forging aluminum
- Rimless structure design, fit to high –end oriented market demands

Product Feature:

- Module structure, adapted to different to different LED light source and beam angle
- Trim less Structure design, adjustable or non adjustable for option, die –cast lamp body, simple but elegant
- Anti- glare tech, comfort and non glare lighting effect
- Different drivers for option , non – flicker, smart control etc.
- Tilt able and downlight function design with various colorful decorative reflector.
- IP 20, IP44 For Option
- Finishing white, gold, available as standard
- Suitable for wall washing
- Life span up to 50,000 hours

Special Characteristics:

- 30° Adjustable in horizontal
- UGR<10
- Different color option for anti-glare ring




● Gray ● Black ○ White

CEILING RECESSED DOWN LIGHTS

LED Colour Temperature

- 2700K
- 3000K
- 4000K



Item	Power	Dimension	Cut out	Lumens(lm)
MOD-A-05-9	8W	Ø90x76	Ø75	750
MOD-A-05-12	12W	Ø90x76	Ø75	1116
MOD-B-05-15	15W	Ø115X100	Ø100	1395
MOD-B-05-20	20W	Ø115X100	Ø100	1860
MOD-C-05-25	25W	Ø140X112	Ø125	2325
MOD-C-05-30	30W	Ø140X112	Ø125	2790
MOD-D-05-35	35W	Ø165X132	Ø150	3255
MOD-D-05-40	40W	Ø165X132	Ø150	3720

